

ZHC & ZDUW Series

Capacity: 1 to 25 tons

Quality Rigging & Machinery Moving Supply

Use the safe dependable toe jacks and speed rollers to safely lift and move a heavy load in a low clearance situation. Super low height (the lowest in the industry) toe jacks, ease operation under the most difficult situations. These are the best choice for lifting heavy machinery and cargo, especially when installing industrial machinery, relocating shipyard equipment, or during bridge and plant construction. Range in capacity. Used these toe jacks with the "industrial strength" speed roller for moving heavy, oversized equipment and cargo safely. All-steel rollers securely support and transport extra heavy loads in a safe, worker-wise manner. They come in sizes to easily handle 1 to 25 tons.



Model: ZHC-2V

Model: ZHC-12VP

Model: ZHC-5V

Combo: ZHC-5VP w/ ZAP-40 air pump



Fig. 12



Fig. 13

Toe Jacks

1. 360° turn lever socket for operation at any direction. (Fig. 12)
2. Low toe height is ideal for use where clearance is tight.
3. Designed for fine adjustments. Ideal for delicate work such as installation of precision machines.
4. Welded steel construction prevents oil leakage and a special heat treatment that reduces metal fatigue.
5. Optional coupler connection port available upon request for 5-25 tons toe jacks, which make these toe jacks ready to be used with any air pump. (Fig. 13)

Model Number	Capacity (Tons)	Min. Ht. (in)		Max Ht. (in)		Ram Lift (in)	Toe Area (in)	Base Area (in)	Ship Wt. (lbs)
		Toe	Head	Toe	Head				
ZHC-2V	2	5/8	7 7/8	5 1/16	12 3/8	4 7/16	2 x 2	5 x 7	21
ZHC-5V	5	7/8	9 3/8	5 1/2	14 1/4	4 3/4	2 1/4 x 3	7 1/2 x 10 1/2	53
ZHC-12V	12	1 1/8	12 7/8	6 3/4	18 1/2	5 5/8	2 1/8 x 4	9 1/2 x 11 1/2	84
ZHC-15V	15	1 1/8	13 1/4	6 5/8	18 3/4	5 1/2	2 3/8 x 3 3/8	9 1/2 x 11 1/2	93
ZHC-25V	25	1 1/4	14 3/4	6 3/4	21 1/4	5 1/2	2 3/8 x 4 3/4	12 x 12	165